



POSTS SET IN CONCRETE

**NOTES:**

STANDARD LOCATION DIMENSIONS ABOVE UNLESS DIRECTED OTHERWISE BY CITY ENGINEERING  
 STREET NAME SIGNS ARE TO BE PLACED ON SOUTH WEST CORNER WHERE POSSIBLE  
 CONTRACTOR TO SUPPLY STREET SIGNS,

**POST MOUNTED STREET SIGN SPECIFICATIONS LOCAL STREETS WITH SPEED LIMITS OF 25 MPH OR LESS:**

6" EXTRUDED BLADE BY REQUIRED LENGTH DEPENDING UPON LENGTH OF NAME WITH A 24" MINIMUM.  
 STREET NAME SHALL APPEAR ON BOTH SIDES OF SIGN

**COLOR:**

GREEN BACKGROUND 3M #3930 SERIES HIGH INTENSITY PRISMATIC (HIP).

WHITE LETTERING 3M #3930 SERIES HIGH INTENSITY PRISMATIC (HIP) .

HEIGHT OF LETTERS TO BE 4" INCH UPPER AND LOWER CASE SERIES "B", PREFIX AND SUFFIX TO BE 4 " INCH SERIES "B" UPPER AND LOWER CASE LETTERS. SUFFIX LESS THAN 5 LETTERS SHALL NOT BE ABBREVIATED.

**POST MOUNTED STREET NAME SIGN SPECIFICATIONS FOR ARTERIAL/COLLECTOR STREETS WITH SPEED LIMITS OF 30 MPH OR ABOVE.**

9" EXTRUDED BLADE BY REQUIRED LENGTH DEPENDING ON LENGTH OF NAME, 24" MINIMUM.

STREET NAME SHALL APPEAR ON BOTH SIDES OF SIGN.

**COLOR:**

GREEN BACKGROUND 3M 3930 SERIES HIGH INTENSITY PRISMATIC (HIP)

WHITE LETTERING 3M #3930 SERIES HIGH INTENSITY PRISMATIC (HIP)

HEIGHT OF LETTER TO BE 6" INCH UPPER AND LOWER CASE SERIES "B", PREFIX AND SUFFIX TO BE (6) INCH SERIES "B" UPPER AND LOWER CASE LETTERS. SUFFIX LESS THAN 5 LETTERS SHALL NOT BE ABBREVIATED.

**SPECIFICATIONS FOR STREET SIGN HARDWARE:**

SIGNS SHALL BE MOUNTED ON 2"X2" BREAKAWAY POSTS IN SOCKET WITH 8" DIA. CONCRETE 30" DEEP FOOTING (SEE SIGN DETAIL DRAWING).

STREET SIGNS SHALL BE MOUNTED TO POST WITH 2"X2" POST CAP FOR EXTRUDED SIGNS.

STOP SIGNS TO HAVE BOTH STREET NAMES LOCATED ON TOP (BOTH SIDES).

STOP SIGNS SHALL BE 30"X30" R-1-1 ON SHEET ALUMINUM (UNLESS OTHERWISE NOTED).

(SEE ODOT STD. SPECS. SECTION 00940.41).



**STOP & STREET SIGN  
 TYPICAL INSTALLATION**

ENGINEERING  
 DEPARTMENT  
 1924 COUNCIL STREET  
 P.O. BOX 326  
 FOREST GROVE, OR 97116

DRAWING NO.  
 208

SCALE  
 NONE